

BEST AVAILABLE COPY

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application.

Listing of Claims:

1. (Currently Amended) A high-level synthesis method, comprising:
 - generating a CDFG (Control Data Flow Graph) based on an input file describing a behavior of a digital circuit;
 - scheduling the CDFG by allocating each node of the CDFG generated in the CDFG generation, expressing contents of processing, to a time synchronized with a clock called a Step, based on the CDFG and a constraint condition of the digital circuit described in a constraint file;
 - generating initial allocation information representing how resources for constituting the digital circuit are allocated to respective nodes of the CDFG scheduled in the scheduling and initial circuit information representing a connecting relationship between the resources;
 - modifying the initial allocation and initial circuit information based on resource-level layout information representing a layout of the resources, and based on circuit information representing a connecting relationship between the resources; and
 - outputting the circuit information generated/modified in the allocation and circuit information generation/modification.

2. (Currently Amended) The high-level synthesis method according to claim 1, wherein the allocation and circuit information generation/modification comprises:
 - ~~generating initial allocation information representing how the resources are allocated to the respective nodes of the CDFG scheduled in the scheduling and initial circuit information representing a connecting relationship between the resources;~~
 - generating the resource-level layout information, based on the initial circuit information generated in the initial allocation and initial circuit information generation;
 - generating corrected allocation information representing how an allocation of the resources with respect to the respective nodes of the CDFG is changed and corrected circuit information representing how the connecting relationship between the resources is changed, based on the initial allocation information generated in the initial allocation and initial circuit

BEST AVAILABLE COPY

information generation and the resource-level layout information; and

minutely correcting the resource-level layout information, based on the corrected circuit information generated in the corrected allocation and corrected circuit information generation, wherein

the corrected allocation and corrected circuit information generation, and the resource-level layout minute correction are performed repeatedly until a predetermined standard is satisfied, and

in the corrected allocation and corrected circuit information generation, corrected allocation information representing how an allocation of the resources with respect to the respective nodes of the CDFG is changed and corrected circuit information how the connecting relationship between the resources is changed, are generated based on the resource-level layout information and the corrected allocation information previously generated.

3. (Original) The high-level synthesis method according to claim 2, wherein the allocation information contains hardware resource allocation information and lifetime information of hardware resources.
4. (Original) The high-level synthesis method according to claim 1, wherein the resource-level layout information is distance information of an inter-resource connecting line.
5. (Original) The high-level synthesis method according to claim 1, wherein the resource-level layout information is congestion degree information in a layout region of an inter-resource connecting line.
6. (Original) The high-level synthesis method according to claim 1, wherein the resource-level layout information is inter-macro connecting line information expressed by any function composed of distance information of an inter-resource connecting line and congestion degree information in a layout region of an inter-resource connecting line.
7. (Original) The high-level synthesis method according to claim 1, wherein the resource-level layout information includes a layout influence degree as a coefficient.

BEST AVAILABLE COPY

8. (Original) The high-level synthesis method according to claim 2, wherein the resources are allocated to the respective nodes of the CDFG so as to minimize shared hardware resources in the initial allocation and initial circuit information generation, and
an allocation of the resources with respect to the respective nodes of the CDFG is changed so that hardware resource separately implemented are shared in the corrected allocation and corrected circuit information generation.
9. (Original) The high-level synthesis method according to claim 2, wherein the resources are allocated to the respective nodes of the CDFG so as to maximize shared hardware resources in the initial allocation and initial circuit information generation, and
shared hardware resources are allocated separately in the corrected allocation and corrected circuit information generation.
10. (Original) The high-level synthesis method according to claim 2, wherein, in the corrected allocation and corrected circuit information generation, an arrangement distribution variation in a layout region of memory resources is calculated, synthesis ease of a synchronization clock circuit is estimated based on the arrangement distribution variation in a layout region of the memory resources, and sharing with high synthesis ease is selected when the memory resources are shared.
11. (Original) The high-level synthesis method according to claim 10, wherein the arrangement distribution variation in the layout region of the memory resources is a variation in number of the memory resources belonging to each region obtained by dividing the layout region into a plurality of regions.
12. (Original) The high-level synthesis method according to claim 10, wherein the arrangement distribution variation in the layout region of the memory resources is a total of variations calculated for each hierarchy obtained by dividing the layout region hierarchically.
13. (Currently Amended) The high-level synthesis method according to claim 2, wherein the

resources are allocated to the respective nodes of the CDFG so as to maximize shared hardware resources in the initial allocation and initial circuit information generation,

the shared hardware resources are separately allocated in the corrected allocation and corrected circuit information generation, and

the allocation and circuit information modification generation further includes changing the allocation by allowing the hardware resources divided in the corrected allocation and corrected circuit information generation to be shared with the hardware resources that are not shared in the initial allocation and initial circuit information generation.

14. (Original) The high-level synthesis method according to claim 13, wherein the resource-level layout information includes a layout influence degree as a layout influence coefficient, and the corrected allocation and corrected circuit information generation and the allocation changing are repeatedly performed while the layout influence coefficient is corrected in stages.

15. (Original) The high-level synthesis method according to claim 2, wherein the resource-level layout information minutely corrected in the resource-level layout minute correction is further output in the outputting.